



STOPGAP P141

Primer for Non-Absorbent Surfaces

PRODUCT DATA

INTRODUCTION

STOPGAP P141 is an acrylic primer designed to promote adhesion and application characteristics of STOPGAP smoothing compounds to non-absorbent subfloors. STOPGAP P141 contains recycled uPVC pulver that dries to a hard, textured surface to enhance bond performance.

STOPGAP P141 is recommended for use over non-absorbent surfaces such as ceramic tiles, treated power floated concrete and STOPGAP waterproof surface membranes. STOPGAP P141 is also recommended prior to the application of STOPGAP 600 over non-absorbent surfaces when applied at thicknesses greater than 20mm.

It is suitable for use over normal underfloor heating and is pigmented yellow for visual control of coverage uniformity.

PREPARATION

Floor surfaces must be suitably prepared: sound, smooth, dry (<75% RH) and free from contaminants that may prevent adhesion. The temperature of the floor must be a minimum of 5°C when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before, during and after application. Ensure the subfloor is dry and incorporates an effective damp proof membrane.

For detailed information, request our Subfloor Preparation Guide.

APPLICATION/COVERAGE

SHAKE WELL BEFORE USE. DO NOT DILUTE.

Apply the primer directly to the floor at approximately 13m² per litre. Do not extend coverage as this may affect adhesion properties. Avoid puddling in depressions as this will affect drying times.

DRYING TIME

From 15 minutes at 20°C. Lower temperatures, damp ambient conditions and poor airflow will significantly extend this time. The use of a fan is recommended to reduce drying times.

PRECAUTIONS

Avoid excessive trafficking of the subfloor once the primer has dried.

TOOLS

Short or medium pile roller. Wash with warm water immediately after use and store in a polythene bag.

STORAGE

Store between 5°C and 25°C. Protect from frost.

SHELF LIFE

12 months in unopened containers and stored under good conditions.

TECHNICAL INFORMATION

Colour	Yellow
Coverage Rate (Approx.)	Applied neat to non-absorbent : 65m ² Rates will vary based on the condition of the subfloor
Drying Time (Approx.)	From 15 minutes at 20°C on non-absorbent subfloors

HOW MUCH MATERIAL?

PACK SIZE	COVERAGE PER UNIT
5 litres neat	65m ² (max)

The coverage rates will depend on the condition and absorbency of the subfloor.



FEATURES

- Textured finish
- Fast drying
- Pigmented to provide coverage control
- Suitable for use with F. Ball marine applications

PACKAGING

5 litre bottle

HEALTH AND SAFETY ADVICE

This product is classified. Obtain the relevant Safety Data Sheets and follow the advice given. These can be found at www.f-ball.com alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and confirm this data sheet is current please contact Technical Service Department.

For further information about F. Ball products or more detailed technical assistance, please contact:

F. Ball and Co. Ltd.
Churnetside Business Park
Station Road, Cheddleton, Leek
Staffordshire ST13 7RS
United Kingdom

Tel: +44 (0) 1538 361633
Email: mail@f-ball.co.uk

www.f-ball.com