



DECLARATION OF PERFORMANCE

No. FB179-CPR-26-03-2021

Stopgap Micro Rapid

| | |
|---|--|
| Unique identification code of the product-type: | Stopgap Micro Rapid |
| Intended use/es: | Cementitious screed material for internal flooring applications |
| Manufacturer: | F. Ball and Co. Ltd., Churnetside Business Park, Station Road, Cheddleton, Leek, Staffordshire, ST13 7RS, UK |
| Approved body/ies: | Not applicable |

| Declared performance/s: | | | |
|---------------------------------|-------------|--|--------------------------------|
| Essential characteristics | Performance | Assessment of verification of constancy of performance | Designated standard |
| Reaction to fire | E | System 4 | Commission Decision 2010/85/EU |
| Release of corrosive substances | CT | System 4 | EN 13813:2002 |
| Water permeability | NPD | | |
| Water vapour permeability | NPD | | |
| Mechanical resistance | | | |
| Compressive strength | C16 | | |
| Flexural strength | F6 | | |
| Sound insulation | | | |
| Sound absorption | NPD | | |
| Thermal resistance | NPD | | |
| Chemical resistance | NPD | | |

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Stuart Whiteley
Development Manager

At Leek on 26 April 2021

Note: Information on the content of substances concerning the Registration, Evaluation, Authorisation, and Restriction of Chemicals (UK REACH), is indicated in the safety data sheet available on the website together with this current declaration of performance.