

# COMPLIANCE DATASHEET

## STYCCOBOND F54

A solvent free emulsion adhesive for installing linoleum floor coverings.



Tested to the standards of the International Marine Organisation and approved for use in marine floor installations

**Identification of Hazards** : This product is not classified as hazardous according to Regulation EC 1272/2008.

### Indoor Air Quality (VOC)

EMICODE EC 1 PLUS – very low emission



### LEED

VOC test according to South Coast Air Quality Management District Rule #1168

In house testing to ASTM D2369 Standard Test Method for Volatile Content of Coatings and Adhesives: VOC emissions met

**VOC level (g/l less water)**

0

**VOC limit (g/l less water)**

50

### BREEAM; BS EN 13999-1:2013

In-house testing to the test method described in BS EN 13999 parts 2-4

Product does not contain carcinogenic or sensitising volatile substances

### Life Cycle Assessment (LCA)

LCA according to ISO 14040/44 : EPD according to EN 15804

Functional unit (FU) 1kg product; cradle - gate

Model EPD available on request.

### REACH Directive 1907/2006/EC

Product does not contain any SVHC in concentrations greater than 0.1% (w/w)

### Explosive Precursors EU Regulation 98/2013

Product does not contain explosive precursors above the limit values laid in Annex I of the regulation.

### Air Pollution Control (Volatile Organic Compounds) Regulations – Hong Kong

Not Tested

