

COMPLIANCE DATASHEET

STYCCOBOND F60

A solvent based contact adhesive.

Identification of Hazards : This product is classified as hazardous according to Regulation EC 1272/2008. Obtain the relevant Safety Data Sheets and follow the advice given.

Indoor Air Quality (VOC)

Not tested

LEED

VOC test according to South Coast Air Quality Management District Rule #1168

In house testing to ASTM D2369 Standard Test Method for Volatile Content of Coatings and Adhesives: VOC emissions not met

BREEAM; BS EN 13999-1:2013

In-house testing to the test method described in BS EN 13999 parts 2-4

Product does not comply in its wet state. However, it should be noted that once the adhesive has cured, it is considered to be inert.

Life Cycle Assessment (LCA)

LCA according to ISO 14040/44 : EPD according to EN 15804

Functional unit (FU) 1kg product; cradle - gate

Model EPD available on request.

REACH Directive 1907/2006/EC

Product does not contain any SVHC in concentrations greater than 0.1% (w/w)

Explosive Precursors EU Regulation 98/2013

Product does not contain explosive precursors above the limit values laid in Annex I of the regulation.

Air Pollution Control (Volatile Organic Compounds) Regulations – Hong Kong

Not Tested

