

# **COMPLIANCE DATASHEET**

#### STYCCOBOND F84

A two-part reactive epoxy adhesive designed for installing a wide range of sheet floorcoverings onto Stopgap Isolator Membrane and other suitable substrates.

**Identification of Hazards :** This product is classified as hazardous according to Regulation EC 1272/2008. Obtain the relevant Safety Data Sheets and follow the advice given.

## **Indoor Air Quality (VOC)**

Not tested

### **LEED**

VOC test according to South Coast Air Quality Management District Rule #1168

In house testing to ASTM D2369 Standard Test Method for Volatile Content of Coatings and Adhesives: VOC emissions met

V O O OTTIONOTO THO	
VOC level (g/l less water)	VOC limit (g/l less water)
<1	50

### **BREEAM**; BS EN 13999-1:2013

In-house testing to the test method described in BS EN 13999 parts 2-4

Product does not contain carcinogenic or sensitising volatile substances

## Life Cycle Assessment (LCA)

LCA according to ISO 14040/44: EPD according to EN 15804

Functional unit (FU) 1kg product; cradle - gate

Model EPD available on request.

#### REACH Directive 1907/2006/EC

Product does not contain any SVHC in concentrations greater than 0.1% (w/w)

## **Explosive Precursors EU Regulation 98/2013**

Product does not contain explosive precursors above the limit values laid in Annex I of the regulation.

# Air Pollution Control (Volatile Organic Compounds) Regulations – Hong Kong

Not tested.







Document No: 2047 Issue: 1 Date: 27 June 2016