



# STYCCOCLEAN SOLVENT

*Degreaser and Cleaner*

## PRODUCT DATA

### INTRODUCTION

**STYCCOCLEAN SOLVENT** is a fast drying, non-flammable solvent used for the removal of contaminants such as grease and oil from the back of floorcoverings and accessories prior to installation. It also assists in the removal of some adhesives from the surface of carpets and other floorcoverings.

STYCCOCLEAN SOLVENT can be used on most types of carpets and floorcoverings, covings and nosings etc, made linoleum, rubber, vinyl and metal. It can also be used for cleaning tools after use.

### APPLICATION

**Cleaning floorings and accessories** – Dampen a clean cloth with the solvent and rub the area to be cleaned until all of the contamination has been removed. Take care not to use too much solvent on rubber, linoleum, vinyl or accessories as this may cause damage. When cleaning the back of floorings or accessories, allow all traces of the solvent to evaporate before commencing installation.

**Removing adhesive from carpet** – Apply the solvent gently with a piece of clean cloth until the adhesive has been softened, then remove the adhesive using a small stiff bristle brush. Take care not to rub the softened adhesive into the carpet pile. When cleaning a large area, lay the wetted cloth on the patch of adhesive and cover with a basin, metal foil or polythene to retard evaporation of the solvent whilst the adhesive is softening. More than one application may be necessary.

### PRECAUTIONS

STYCCOCLEAN SOLVENT may damage floorcoverings if left in contact for too long. Test before use to ensure that the solvent does not damage the material or affect the colour stability. Do not use on asphalt, tarmac or other materials that may be sensitive to the solvent. Do not allow the cleaner to penetrate the joints between floor tiles. Do not apply onto a hot surface or any incandescent material.

### TOOLS

Clean absorbent white cloth. Small stiff bristle brush.

### STORAGE

Store between 5°C and 30°C. Protect from frost.

### SHELF LIFE

24 months in unopened containers and stored under good conditions.

### PACKAGES

500ml tin.

### FEATURES

- Fast drying
- Non-flammable
- Easy to apply
- Removes grease, oil and some adhesives

### HEALTH AND SAFETY ADVICE

This product is classified. Obtain the relevant Safety Data Sheet and follow the advice given. These can be found at [www.f-ball.com](http://www.f-ball.com) alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Services Department.

**For further information about F. Ball products or more detailed technical assistance, please contact:**

**F. Ball and Co. Ltd.**  
Churnetside Business Park  
Station Road, Cheddleton, Leek  
Staffordshire ST13 7RS  
United Kingdom

Tel: +44 (0) 1538 361633  
Email: [mail@f-ball.co.uk](mailto:mail@f-ball.co.uk)  
[www.f-ball.com](http://www.f-ball.com)