

DECLARATION OF PERFORMANCE

FB011-CPR-14-02-2013

- 1. Product name:** Stopgap 850 Exterior
- 2. Product identification:** Batch number and/or date of manufacture on packaging
- 3. Intended use:** Repair mortar PCC for non-structural repair of concrete structures with low performance requirements in buildings and civil engineering works
- 4. Manufacturer:** F Ball and Co Ltd
Churnetside Business Park
Station Road
Cheddleton
Leek
Staffordshire
ST13 7RS
United Kingdom
- Tel: +44 (0) 1538 361 633
Fax: +44 (0) 1538 361 622
Email: mail@f-ball.co.uk
- 5. Authorised representative:** Not applicable
- 6. AVCP:** System 4, Reaction to fire: System 4
- 7. Notified body (hEN):** Not applicable
- 8. Notified body (ETA):** Not applicable
- 9. Declared performance:**




Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Class R2 ≥ 15 MPa	EN 1504-3:2005
Chloride ion content	$\leq 0,05\%$	EN 1504-3:2005
Adhesive bond	$\geq 0,8$ MPa	EN 1504-3:2005
Thermal compatibility, Part 1: Freeze-thaw	$\geq 0,8$ MPa	EN 1504-3:2005
Slip/ skid resistance	Class III ≥ 55 wet	EN 1504-3:2005
Capillary absorption	$\leq 0,5 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0,5}$	EN 1504-3:2005
Reaction to fire	Class F	EN 13501-1:2007+A1:2009
Dangerous substances	comply with 5.4	EN 1504-3:2005

- 10. Declaration:** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Leek, 24 June 2013


Stuart Whiteley
Development Section Leader – Cement Technology

